


# TNL 20.1040.03/DIM



Colours	Article no.	EAN
white	635973	4043544384607









#### Description

- free-standing luminaire with direct-indirect illumination for uniform and glarefree workplace lighting
- light component: direct 50% / indirect 50%
- direct and indirect light component with separate dimming and switching
- outstanding ease of maintenance
- no UV and thermal emissions
- light-head made from high-gloss acrylic glass (black or white) and aluminium
- rectangular stand made from aluminium
- standard base made from steel St37 (special version ZBB 002 please indicate when ordering)
- switchDIM with memory function (ON/OFF short pushbutton press, dimming UP/DOWN long pushbutton press)
- diffusers for direct light component made from prismatic acrylic glass, diffusers for indirect light component made from clear acrylic glass
- central plug connection to mains (length of connecting cable: approx. 3000 mm), cable in the same colour as the luminaire
- ballast (LED converter) integrated in the stand

### Standard options



### Lighting data / Norms

Lamps EPREL light sources

Lifetime

System power Luminaire luminous flux System efficiency Module efficiency UGR class Supply voltage Protection class Type of protection LED linear / CRI 80 / 4000 K 833900 L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h 102.0 W 8950 lm 87.74 lm/W 188.50 lm/W ≤22 220 - 240 V / 50 - 60 Hz I IP20


Dimensions / Weights

Length	650 mm
Width	160 mm
Height	1931 mm
Net weight	20.92 kg
Gross weight	21.98 kg
Gross weight	21.98 kg

## Free-Standing Luminaires · Trentino II Free-Standing

## TNL 20.1040.03/DIM

Trentino II Standing (1xLED 102W 840/4000K 8950lm)



	C0	C90	C180	C270
0°	258	258	258	258
30°	214	216	214	216
60°	43	41	43	41
90°	10	2	10	2
120°	60	57	60	57
150°	171	164	171	164
180°	79	79	79	79
cd / 1000 lm				

LOVE TO SHINE

LDC unsuitable for cone representation. The C0 angle is oversized.

η	LED		
Efficiency	88 lm/W ↓ 52% / † 48%		
Direct/Indirect			
System Power	102 W		
UGR	X=4H, Y=8H		
Reflection factors	70/50/20		
UGR C0/C180	20.3		
UGR C90/C270	18.8		
CIE Flux Codes	64 88 97 52 100		
Ra/CRI	>80		
	LT		

し

#### Accessories



**ZBB 002** luminaire base version 2