



TORL 251.830.25




Colours	Article no.	EAN
silver	661180	4043544700360
black	661211	4043544701053
white	661212	4043544701060



Description

- recessed downlight with protruding light-head
- light-head can be preadjusted in three positions (19/42/65 mm)
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management via housing
- high-tech reflector lense made from PMMA for high luminous efficiency and glare-free lighting
- cylindrical housing made from aluminium
- recessed ring made from sheet steel
- tool-free ceiling mounting via quick-action clamping springs (adjustable ceiling thickness 1 - 20 mm or 10 - 40 mm)
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter) included (external placement)

Standard options



Special options



Lighting data / Norms


Lamps	LED Spot / CRI 80 / 3000 K
EPREL light sources	992480
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	12.0 W
Luminaire luminous flux	1030 lm
System efficiency	85.83 lm/W
Module efficiency	157.83 lm/W
UGR class	≤19
Beam angle	25°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	III
Type of protection	IP20

Dimensions / Weights

Outer diameter	83 mm
Height	88 mm
Cut-out (Ø)	73 mm
Ceiling thickness	1.0 - 20.0 mm
Recessed depth	68 mm
Diameter of light head	48 mm
Net weight	0.50 kg
Gross weight	0.53 kg

TORL 251.830.25

Torpedo 250 (1xLED 12W 827/2700K 1030lm 25 °)



	C0	C90	C180	C270
0°	3638	3638	3638	3638
15°	1611	1611	1611	1611
30°	188	188	188	188
45°	25	25	25	25
60°	8	8	8	8
75°	1	1	1	1
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]	Illuminance [lx]
C0-C180 Plane		
3.0	1.48	416.4
6.0	2.97	104.1
9.0	4.45	46.3
12.0	5.93	26.0
15.0	7.41	16.7

η	LED
Efficiency	86 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	16.7
UGR C90/C270	16.7
CIE Flux Codes	97 99 100 100 100
Ra/CRI	>80

LTS