


TORL 251.830.40




Colours	Article no.	EAN
silver	661213	4043544701077
black	661214	4043544701084
white	661215	4043544701091



Description

- recessed downlight with protruding light-head
- light-head can be preadjusted in three positions (19/42/65 mm)
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management via housing
- high-tech reflector lense made from PMMA for high luminous efficiency and glare-free lighting
- cylindrical housing made from aluminium
- recessed ring made from sheet steel
- tool-free ceiling mounting via quick-action clamping springs (adjustable ceiling thickness 1 - 20 mm or 10 - 40 mm)
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter) included (external placement)

Standard options



Special options



Lighting data / Norms

Lamps	LED Spot / CRI 80 / 3000 K
EPREL light sources	992480
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	12.0 W
Luminaire luminous flux	1100 lm
System efficiency	91.66 lm/W
Module efficiency	157.83 lm/W
UGR class	≤22
Beam angle	40°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	III
Type of protection	IP20


Dimensions / Weights

Outer diameter	83 mm
Height	88 mm
Cut-out (Ø)	73 mm
Ceiling thickness	1.0 - 20.0 mm
Recessed depth	68 mm
Diameter of light head	48 mm
Net weight	0.50 kg
Gross weight	0.53 kg

TORL 251.830.40

Torpedo 250 (1xLED 12W 827/2700K 1100lm 40 °)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	1942	1942	1942	1942
15°	1365	1365	1365	1365
30°	340	340	340	340
45°	47	47	47	47
60°	10	10	10	10
75°	1	1	1	1
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	2.16	237.3
6.0	4.32	59.3
9.0	6.48	26.4
12.0	8.65	14.8
15.0	10.81	9.5

η	LED
Efficiency	92 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	20.9
UGR C90/C270	20.9
CIE Flux Codes	95 99 100 100 100
Ra/CRI	>80

LTS