


TORL 351.827.35/DALI



Colours	Article no.	EAN
silver	661253	4043544701480
black	661254	4043544701497
white	661255	4043544701503




Description

- recessed downlight with protruding light-head
- light-head can be preadjusted in three positions (19/58/98 mm)
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management via housing
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- cylindrical housing made from aluminium
- recessed ring made from sheet steel
- clear safety glass
- tool-free ceiling mounting via quick-action clamping springs (adjustable ceiling thickness 1 - 20 mm or 10 - 40 mm)
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter DALI, dimmable) included (external placement)

Standard options



Special options



Lighting data / Norms


Lamps	LED Spot / CRI 80 / 2700 K
EPREL light sources	848120
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	
System power	13.0 W
Luminaire luminous flux	1250 lm
System efficiency	96.15 lm/W
Module efficiency	127.18 lm/W
UGR class	≤19
Beam angle	35°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	III
Type of protection	IP20

Dimensions / Weights

Outer diameter	115 mm
Height	118 mm
Cut-out (Ø)	100 mm
Ceiling thickness	1.0 - 20.0 mm
Recessed depth	110 mm
Diameter of light head	80 mm
Net weight	0.85 kg
Gross weight	0.89 kg

TORL 351.827.35/DALI

Torpedo 350 (1xLED 13W 827/2700K 1250lm 35 °)



	C0	C90	C180	C270
0°	2566	2566	2566	2566
15°	1406	1406	1406	1406
30°	364	364	364	364
45°	3	3	3	3
60°	0	0	0	0
75°	0	0	0	0
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	1.73	356.4
6.0	3.45	89.1
9.0	5.18	39.6
12.0	6.91	22.3
15.0	8.63	14.3

η	LED
Efficiency	96 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	13 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	16.9
UGR C90/C270	16.9
CIE Flux Codes	100 100 100 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting



ZBW 85
honeycomb louvre