


TPSA 180.1140.11



Description

- surface-mounted downlight for general lighting
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management via housing
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- housing cylinder made from die-cast aluminium
- sheet steel mounting ring with bayonet catch and safety rope for screw mounting
- 5-pole terminal block
- ballast (LED converter) integrated

Standard options




Lighting data / Norms

Lamps	LED Modul / CRI 80 / 4000 K
EPREL light sources	891017
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	
System power	9.5 W
Luminaire luminous flux	1140 lm
System efficiency	120.00 lm/W
Module efficiency	122.35 lm/W
UGR class	≤16
Beam range	Wide Flood
Beam angle	60°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights

Outer diameter	180 mm
Height	200 mm
Net weight	2.99 kg
Gross weight	3.46 kg

Colours	Article no.	EAN
silver	635912	4043544383983
white	635913	4043544383990
black	642411	4043544483034




TPSA 180.1140.11

TPSA 180.1140.11


Topas | Surface-mounted (1xLED 10W 840/4000K 1140lm)

— C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	1177	1177	1177	1177
15°	1008	1008	1008	1008
30°	579	579	579	579
45°	48	48	48	48
60°	0	0	0	0
75°	0	0	0	0
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]



η	LED
Efficiency	114 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	10 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	14.4
UGR C90/C270	14.4
CIE Flux Codes	97 100 100 100 100
Ra/CRI	>80

LTS