


VTFS-R 101.827/DALI



Description

- recessed downlight for general lighting
- very low installation depth
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- front/recessed ring and heat sink made from die-cast aluminium
- microprism diffuser opal
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- luminaire and ballast permanently connected via cable (length: 500 mm), ballast ready for mains connection
- ballast (LED converter DALI, dimmable) included (external placement)

Standard options




Lighting data / Norms




Lamps	LED Modul / CRI 80 / 2700 K
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	
System power	14.3 W
Luminaire luminous flux	1040 lm
System efficiency	72.72 lm/W
UGR class	≤28
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	II
Type of protection	IP44

Dimensions / Weights

Outer diameter	158 mm
Height	73 mm
Cut-out (Ø)	142 mm
Ceiling thickness	1.0 - 25.0 mm
Recessed depth	70 mm
Net weight	0.68 kg
Gross weight	0.72 kg




Colours	Article no.	EAN
black	641463	4043544459091
silver	641464	4043544459107
white	641465	4043544459114



VTFS-R 101.827/DALI

Vale-Tu Flat Small | Recessed (1xLED 14W 827/2700K 1040lm)



	C0	C90	C180	C270
0°	486	486	486	486
15°	449	449	449	449
30°	355	355	355	355
45°	230	230	230	230
60°	119	119	119	119
75°	39	39	39	39
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	5.68	56.2
6.0	11.37	14.0
9.0	17.05	6.2
12.0	22.74	3.5
15.0	28.42	2.2

η	LED
Efficiency	74 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	14 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	25.9
UGR C90/C270	25.9
CIE Flux Codes	58 86 98 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting



ZDAR 145.165-225
compensation ring for ceiling cut-outs from 165 to 225 mm