


VTRM 10.0527.25/DALI



Colours	Article no.	EAN
silver	641886	4043544462152



Description

- recessed spotlight with round recessed funnel
- reflector lens pivots through 20°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- recessed funnel and heat sink made from die-cast aluminium
- high-tech reflector lens made from PMMA for high luminous efficiency and glare-free lighting
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- luminaire and ballast permanently connected via cable (length: 500 mm), ballast ready for mains connection
- ballast (LED converter DALI, dimmable) included (external placement)

Standard options



Special options



Lighting data / Norms

Lamps	LED Spot / CRI 80 / 2700 K
EPREL light sources	871010
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	12.0 W
Luminaire luminous flux	1020 lm
System efficiency	85.00 lm/W
Module efficiency	120.72 lm/W
UGR class	≤19
Beam range	Medium Flood
Beam angle	27°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	II
Type of protection	IP40


Dimensions / Weights

Outer diameter	90 mm
Height	103 mm
Cut-out (Ø)	78 mm
Ceiling thickness	10.0 - 15.0 mm
Recessed depth	117 mm
Diameter of light head	50 mm
Net weight	0.53 kg
Gross weight	0.59 kg

VTRM 10.0527.25/DALI

Vale-Tu Round Medium (1xLED 12W 827/2700K 1020lm)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	3657	3657	3657	3657
15°	1545	1545	1545	1545
30°	207	207	207	207
45°	30	30	30	30
60°	15	15	15	15
75°	0	0	0	0
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	1.44	414.4
6.0	2.88	103.6
9.0	4.33	46.0
12.0	5.77	25.9
15.0	7.21	16.6

η	LED
Efficiency	85 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	18.3
UGR C90/C270	18.3
CIE Flux Codes	95 99 100 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series