



VTRM 12.0527.60/DALI



| Colours | Article no. | EAN |
|---------|-------------|---------------|
| black | 663770 | 4043544729071 |



Description

- recessed spotlight with round recessed funnel
- reflector lens pivots through 20°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- recessed funnel and heat sink made from die-cast aluminium
- high-tech reflector lens made from PMMA for high luminous efficiency and glare-free lighting
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- luminaire and ballast permanently connected via cable (length: 500 mm), ballast ready for mains connection
- ballast (LED converter DALI, dimmable) included (external placement)

Standard options



Special options



Lighting data / Norms


| | |
|-------------------------|---|
| Lamps | LED Spot / CRI 80 / 2700 K |
| EPREL light sources | 871010 |
| Lifetime | L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h |
| System power | 12.0 W |
| Luminaire luminous flux | 970 lm |
| System efficiency | 80.83 lm/W |
| Module efficiency | 120.72 lm/W |
| UGR class | ≤28 |
| Beam range | Wide Flood |
| Beam angle | 59° |
| Supply voltage | 220 - 240 V / 50 - 60 Hz |
| Protection class | II |
| Type of protection | IP40 |

Dimensions / Weights

| | |
|------------------------|----------------|
| Outer diameter | 90 mm |
| Height | 103 mm |
| Cut-out (Ø) | 78 mm |
| Ceiling thickness | 10.0 - 15.0 mm |
| Recessed depth | 117 mm |
| Diameter of light head | 50 mm |
| Net weight | 0.53 kg |
| Gross weight | 0.59 kg |

VTRM 12.0527.60/DALI

Vale-Tu Round Medium (1xLED 12W 827/2700K 970lm)



| | C0 | C90 | C180 | C270 |
|--------------|------|------|------|------|
| 0° | 1004 | 1004 | 1004 | 1004 |
| 15° | 832 | 832 | 832 | 832 |
| 30° | 490 | 490 | 490 | 490 |
| 45° | 119 | 119 | 119 | 119 |
| 60° | 35 | 35 | 35 | 35 |
| 75° | 17 | 17 | 17 | 17 |
| 90° | 0 | 0 | 0 | 0 |
| cd / 1000 lm | | | | |

| Offset [m] | Cone width [m] | Illuminance [lx] |
|------------|----------------|------------------|
| 3.0 | 3.40 | 108.2 |
| 6.0 | 6.79 | 27.1 |
| 9.0 | 10.19 | 12.0 |
| 12.0 | 13.59 | 6.8 |
| 15.0 | 16.99 | 4.3 |

| | |
|--------------------|------------------|
| η | LED |
| Efficiency | 81 lm/W |
| Direct/Indirect | ↓ 100% / ↑ 0% |
| System Power | 12 W |
| UGR | X=4H, Y=8H |
| Reflection factors | 70/50/20 |
| UGR C0/C180 | 27.6 |
| UGR C90/C270 | 27.6 |
| CIE Flux Codes | 83 95 99 100 100 |
| Ra/CRI | >80 |

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting