

VTRM 13.0530.35



Description

- recessed spotlight with round recessed funnel
- reflector lens pivots through 20°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- recessed funnel and heat sink made from die-cast aluminium
- high-tech reflector lens made from PMMA for high luminous efficiency and glare-free lighting
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- luminaire and ballast permanently connected via cable (length: 500 mm), ballast ready for mains connection
- ballast (LED converter) included (external placement)

Standard options



Special options



Lighting data / Norms




Lamps	LED Spot / CRI 80 / 3000 K
EPREL light sources	871340
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	12.0 W
Luminaire luminous flux	1120 lm
System efficiency	93.33 lm/W
Module efficiency	128.30 lm/W
UGR class	≤22
Beam range	Flood
Beam angle	38°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	II
Type of protection	IP40

Dimensions / Weights

Outer diameter	90 mm
Height	103 mm
Cut-out (Ø)	78 mm
Ceiling thickness	10.0 - 15.0 mm
Recessed depth	117 mm
Diameter of light head	50 mm
Net weight	0.49 kg
Gross weight	0.52 kg




Colours	Article no.	EAN
white	641915	4043544462442



VTRM 13.0530.35

Vale-Tu Round Medium (1xLED 12W 830/3000K 1120lm Wide-Flood °)



	C0	C90	C180	C270
0°	2029	2029	2029	2029
15°	1362	1362	1362	1362
30°	343	343	343	343
45°	43	43	43	43
60°	14	14	14	14
75°	7	7	7	7
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]	Illuminance [lx]
C0-C180 Plane		
3.0	2.06	252.4
6.0	4.11	63.1
9.0	6.17	28.0
12.0	8.23	15.8
15.0	10.28	10.1

η	LED
Efficiency	93 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.1
UGR C90/C270	22.1
CIE Flux Codes	93 98 100 100 100
Ra/CRI	>80

LTS