


VTSL 10.0540.25/DALI



Description

- recessed spotlight with square recessed funnel
- reflector lens pivots through 20°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- recessed funnel and heat sink made from die-cast aluminium
- high-tech reflector lens made from PMMA for high luminous efficiency and glare-free lighting
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter DALI, dimmable) included (external placement)


Standard options



Special options



Colours	Article no.	EAN
silver	642002	4043544462978





Lighting data / Norms

Lamps	LED Spot / CRI 80 / 4000 K
EPREL light sources	871846
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	12.0 W
Luminaire luminous flux	1150 lm
System efficiency	95.83 lm/W
Module efficiency	132.06 lm/W
UGR class	≤19
Beam angle	25°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	III
Type of protection	IP40

Dimensions / Weights


Length	110 mm
Width	110 mm
Height	108 mm
Cut-out (LxW)	95 x 95 mm
Ceiling thickness	10.0 - 15.0 mm
Recessed depth	122 mm
Diameter of light head	50 mm
Net weight	0.60 kg
Gross weight	0.66 kg



VTSL 10.0540.25/DALI

Vale-Tu Square Large (1xLED 12W 840/4000K 1150lm)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	3667	3667	3667	3667
15°	1509	1509	1509	1509
30°	227	227	227	227
45°	27	27	27	27
60°	6	6	6	6
75°	0	0	0	0
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]

C0-C180 Plane		
3.0	1.42	468.6
6.0	2.83	117.1
9.0	4.25	52.1
12.0	5.66	29.3
15.0	7.08	18.7

η	LED
Efficiency	96 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	17.0
UGR C90/C270	17.0
CIE Flux Codes	97 100 100 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series