

VTSS 12.0530.25



Description

- recessed spotlight with square recessed funnel
- reflector lens pivots through 20°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- recessed funnel and heat sink made from die-cast aluminium
- high-tech reflector lens made from PMMA for high luminous efficiency and glare-free lighting
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter) included (external placement)


Standard options



Special options



Colours	Article no.	EAN
black	642081	4043544464149



Lighting data / Norms

Lamps	LED Spot / CRI 80 / 3000 K
EPREL light sources	871340
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	12.0 W
System power	1010 lm
Luminaire luminous flux	84.16 lm/W
System efficiency	128.30 lm/W
Module efficiency	≤19
UGR class	25°
Beam angle	220 - 240 V / 50 - 60 Hz
Supply voltage	III
Protection class	IP40
Type of protection	

Dimensions / Weights

Length	80 mm
Width	80 mm
Height	98 mm
Cut-out (LxW)	70 x 70 mm
Ceiling thickness	10.0 - 15.0 mm
Recessed depth	112 mm
Diameter of light head	50 mm
Net weight	0.49 kg
Gross weight	0.52 kg



VTSS 12.0530.25

Vale-Tu Square Small (1xLED 12W 830/3000K 1010lm)

