



VTXSXS 10.0530.35/DALI



Colours	Article no.	EAN
silver	642108	4043544482464



Description

- recessed spotlight with square and flush front frame
- reflector lens pivots through 20°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- recessed frame made from die-cast zinc and heat sink made from die-cast aluminium
- high-tech reflector lens made from PMMA for high luminous efficiency and glare-free lighting
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter DALI, dimmable) included (external placement)

Standard options

2700 K	4000 K
--------	--------

Special options



Lighting data / Norms


Lamps	LED Spot / CRI 80 / 3000 K
EPREL light sources	871340
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	12.0 W
Luminaire luminous flux	1160 lm
System efficiency	96.66 lm/W
Module efficiency	128.30 lm/W
UGR class	≤22
Beam angle	35°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	III
Type of protection	IP40

Dimensions / Weights

Length	80 mm
Width	80 mm
Height	76 mm
Cut-out (Ø)	68 mm
Ceiling thickness	10.0 - 15.0 mm
Recessed depth	87 mm
Diameter of light head	50 mm
Net weight	0.58 kg
Gross weight	0.63 kg

VTXSX 10.0530.35/DALI

Vale-Tu Square XSmall (1xLED 12W 830/3000K 1160lm Wide-Flood °)



	C0	C90	C180	C270
0°	1962	1962	1962	1962
15°	1320	1320	1320	1320
30°	330	330	330	330
45°	59	59	59	59
60°	15	15	15	15
75°	5	5	5	5
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	2.05	252.8
6.0	4.10	63.2
9.0	6.15	28.1
12.0	8.19	15.8
15.0	10.24	10.1

η	LED
Efficiency	97 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	21.7
UGR C90/C270	21.7
CIE Flux Codes	93 98 100 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series