


VTXSXS 12.0540.60



Colours	Article no.	EAN
black	663755	4043544728890



Description

- recessed spotlight with square and flush front frame
- reflector lens pivots through 20°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- recessed frame made from die-cast zinc and heat sink made from die-cast aluminium
- high-tech reflector lens made from PMMA for high luminous efficiency and glare-free lighting
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter) included (external placement)

Standard options



Special options



Lighting data / Norms


Lamps	LED Spot / CRI 80 / 4000 K
EPREL light sources	871846
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	12.0 W
Luminaire luminous flux	1100 lm
System efficiency	91.66 lm/W
Module efficiency	132.06 lm/W
UGR class	≤28
Beam angle	60°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	III
Type of protection	IP40

Dimensions / Weights

Length	80 mm
Width	80 mm
Height	76 mm
Cut-out (Ø)	68 mm
Ceiling thickness	10.0 - 15.0 mm
Recessed depth	87 mm
Diameter of light head	50 mm
Net weight	0.54 kg
Gross weight	0.57 kg

VTXSXS 12.0540.60

Vale-Tu Square XSmall (1xLED 12W 840/4000K 1100lm)



	C0	C90	C180	C270
0°	849	849	849	849
15°	727	727	727	727
30°	432	432	432	432
45°	171	171	171	171
60°	53	53	53	53
75°	15	15	15	15
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]	Illuminance [lx]
C0-C180 Plane		
3.0	3.52	103.8
6.0	7.04	26.0
9.0	10.55	11.5
12.0	14.07	6.5
15.0	17.59	4.2

η	LED
Efficiency	92 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	28.2
UGR C90/C270	28.2
CIE Flux Codes	76 94 99 100 100
Ra/CRI	>80

LTS