




CSARL 71.20.25/B




Colours	Article no.	EAN
black	649607	4043544575142
silver	649608	4043544575159
white	649609	4043544575166



Description

- recessed spotlight with conical light-head for special lighting of bakery products
- suitable for lighting of vertical surfaces (shadowless wall lighting up to the ceiling edge)
- light-head rotates through 355° and pivots out through 60°
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management with passive cooling (heat sink made from die-cast aluminium)
- high performance specular aluminium reflector with precise symmetrical beam characteristic for highest luminous efficiency and best glare-free lighting
- front/recessed ring and light-head made from die-cast zinc
- clear safety glass
- tool-free ceiling mounting via quick-action clamping springs (safety rope, automatic adjustment of the ceiling thickness)
- luminaire and ballast permanently connected via cable (length: 500 mm), ballast ready for mains connection
- ballast (LED converter) included (external placement)

Standard options



Special options



Lighting data / Norms

Lamps	LED Spot Bakery / CRI 82
EPREL light sources	832579
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	36.1 W
System power	3630 lm
Luminaire luminous flux	100.55 lm/W
System efficiency	109.90 lm/W
Module efficiency	≤19
UGR class	Medium Flood
Beam range	23°
Beam angle	220 - 240 V / 50 - 60 Hz
Supply voltage	


Protection class	II
Type of protection	IP20

Dimensions / Weights

Outer diameter	175 mm
Height	145 mm
Cut-out (Ø)	158 mm
Ceiling thickness	1.0 - 25.0 mm
Recessed depth	140 mm
Diameter of light head	114 mm
Net weight	2.70 kg

Recessed Spotlights · CSA 71 Round

CSARL 71.20.25/B



LTS
LOVE TO SHINE


Gross weight

284 kg

CSARL 71.20.25/B

CSARL 71.20.25/B

CSA 71 Round (1xLED 36W BAKERY 3630lm 25°)



	C0	C90	C180	C270
0°	3966	3966	3966	3966
15°	1194	1194	1194	1194
30°	384	384	384	384
45°	4	4	4	4
60°	3	3	3	3
75°	2	2	2	2
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]	Illuminance [lx]
C0-C180 Plane		
3.0	1.21	1599.5
6.0	2.42	399.9
9.0	3.62	177.7
12.0	4.83	100.0
15.0	6.04	64.0

η	LED
Efficiency	101 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	36 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.4
UGR C90/C270	19.4
CIE Flux Codes	99 99 100 100 100
Ra/CRI	---

LTS

Accessories



ZDAR 158.200-265
compensation ring for ceiling cut-outs from 200 to 265 mm