Recessed Spotlights · CSA 71 Round

CSARL 71.2030.25/DALI

Colours	Article no.	EAN
black	649646	4043544575531
silver	649647	4043544575548
white	649648	4043544575555







Description

- recessed spotlight with conical light-head
- suitable for lighting of vertical surfaces (shadowless wall lighting up to the ceiling edge)
- light-head rotates through 355° and pivots out through 60°
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management with passive cooling (heat sink made from die-cast aluminium)
- high performance specular aluminium reflector with precise symmetrical beam characteristic for highest luminous efficiency and best glare-free lighting
- front/recessed ring and light-head made from die-cast zinc
- clear and reflection-free EnergyVision safety glass
- tool-free ceiling mounting via quick-action clamping springs (safety rope, automatic adjustment of the ceiling thickness)
- luminaire and ballast permanently connected via cable (length: 500 mm), ballast ready for mains connection
- ballast (LED converter DALI, dimmable) included (external placement)

Standard options

2700 K · 4000 K · BAKERY · SP · WF

Special options

3500 K · CRI 90 SDCM3 · MEAT · PRODUCE · FASHION · TWL · TWPI · MinusBlue · CASAMBI · BETON EINBAU

Lighting data / Norms

Lamps	LED Spot / CRI 80 / 3000 K
EPREL light sources	1070946
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	21.0 W
Luminaire luminous flux	2390 lm
System efficiency	113.80 lm/W
Module efficiency	166.62 lm/W
UGR class	≤19
Beam range	Medium Flood
Beam angle	26°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	II
Type of protection	IP20

Dimensions / Weights

Outer diameter	175 mm
Height	145 mm
Cut-out (Ø)	158 mm
Ceiling thickness	1.0 - 25.0 mm

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 26.04.2024

CSARL 71.2030.25/DALI

Recessed depth	140 mm
Diameter of light head	114 mm
Net weight	2.64 kg
Gross weight	2.82 kg

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 26.04.2024

CSARL 71.2030.25/DALI

CSA 71 Round (1xLED 21W 830/3000K 2390lm 25 °)



	C0	C90	C180	C270
0°	3101	3101	3101	3101
15°	1272	1272	1272	1272
30°	392	392	392	392
45°	6	6	6	6
60°	4	4	4	4
75°	3	3	3	3
90°	0	0	0	0

cd / 1000 lm



η	LED
Efficiency	114 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	21 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	18.0
UGR C90/C270	18.0
CIE Flux Codes	98 99 100 100 100
Ra/CRI	>80

LTS

Accessories

ZB-OR DONGLE
Organic Response IR dongle kit

ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series

ZB-OR-R SENSOR
Organic Response sensor for recessed mounting

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 26.04.2024