
LKDI-P 060.R05.090 OAG



Colours	Article no.	EAN
silver	659994	4043544791894
black	659995	4043544791900
white	659996	4043544791917



Description

- lichtkanal 060 Curved pendant profile for architectural organic lighting design
- can be combined with linear Lichtkanal 060 Direct-Indirect
- high-quality extruded and powder-coated aluminium profile (radius: 513 mm, angle: 90°)
- light control via highly efficient standard foil "opal diffuse" (advantages: no abutting edges, continuous homogeneous light pattern over the entire length of the foil)
- light-inserts and (necessary) accessories to be ordered separately

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at dT = 10 Kelvin.

Lighting data / Norms

Type of protection	IP20

Dimensions / Weights

Length	1278 mm
Width	1278 mm
Height	90 mm
Net weight	3.92 kg
Gross weight	19.12 kg

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024

LKDI-P 060.R05.090 OAG

Accessories



LKDI-P 060.001 OAG/...
Lichtkanal 060 pendant & wall profile without diffuser (made-to-measure), suitable for foils and opal diffuser protruding



LKDI-P 060.001 OAG/1000
Lichtkanal 060 pendant & wall profile without diffuser (length: 1000 mm), suitable for foils and opal diffuser protruding



LKDI-P 060.001 OAG/1500
Lichtkanal 060 pendant & wall profile without diffuser (length: 1500 mm), suitable for foils and opal diffuser protruding



LKDI-P 060.001 OAG/2000
Lichtkanal 060 pendant & wall profile without diffuser (length: 2000 mm), suitable for foils and opal diffuser protruding



LKDI-P 060.001 OAG/3000
Lichtkanal 060 pendant & wall profile without diffuser (length: 3000 mm), suitable for foils and opal diffuser protruding



LKDI-Z 060.100
connection kit with earthing



LKDI-Z 060.103.03/DIM
wire-rope kit with feed-in DALI (5-core, length: 3000 mm)



STRL-LK-Z 070-060.102.00
connector kit linear



STRL-LK060-Z 690.OPDF.03
light-control foil "opal diffuse" (length: 3 m)



STRL-LK060-Z 690.OPDF.05
light-control foil "opal diffuse" (length: 5 m)



STRL-LK060-Z 690.OPDF.10
light-control foil "opal diffuse" (length: 10 m)



STRL-LK060-Z 690.OPDF.15
light-control foil "opal diffuse" (length: 15 m)

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024

LKDI-P 060.R05.090 OAG

Accessories



STRL-LK060-Z690.OPDF.20
light-control foil "opal diffuse"
(length: 20 m)



STRL-LK060-Z690.OPDF.25
light-control foil "opal diffuse"
(length: 25 m)



STRL-LK060-Z690.OPDF.30
light-control foil "opal diffuse"
(length: 30 m)



STRL-LKDI-Z060.001
end covers
(2 pieces)



STRL-LKDI-Z060.104.03
wire-rope kit without feed-in
(length: 3000 mm)

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024

LKDI-P 060.R05.090 OAG

Light inserts



Name	Description
LK-LED 060.1030.R05.090/DALI	3000 K, 1558 mm, 28 W , 3470 lm
LK-LED 060.1040.R05.090/DALI	4000 K, 1558 mm, 28 W , 3620 lm

Name	Description
LK-LED 060.1130.R05.090/DALI	3000 K, 1558 mm, 45 W , 5250 lm
LK-LED 060.1140.R05.090/DALI	4000 K, 1558 mm, 45 W , 5480 lm

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024