

LK-L 060.10830.0985.1/DALI



Description

- light-insert with integrated LED strips
- reflector made from traffic white painted aluminium sheet
- no UV and thermal emissions
- almost all strip light lengths can be realised
- 5-pole through-wiring kit included
- pMMA matt foil for uniform light distribution
- tool-free snapping into Lichtkanal profile via mounting springs
- 5-pole terminal block, pre-fabricated for through-wiring
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at dT = 10 Kelvin.

Standard options

4000 K

Colours	Article no.	EAN
	667836	4043544795380

Special options






Lighting data / Norms

Lamps	LED linear / CRI 80 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	14.5 W
Luminaire luminous flux	max. 2290 lm
System efficiency	150.34 lm/W
Module efficiency	193.00 lm/W
UGR class	≤28
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I

Dimensions / Weights


Length	985 mm
Width	50 mm
Height	37 mm
Net weight	0.84 kg
Gross weight	0.88 kg



LK-L 060.10830.0985.1/DALI

LK-L 060.10830.0985.1/DALI

Lichtkanal 060 | Light-Insert (Wallwasher nanoOptix, 1xLED 15W 830/3000K 2180lm)



	C0	C90	C180	C270
0°	383	383	383	383
15°	295	342	826	342
30°	210	258	485	258
45°	109	189	193	189
60°	72	112	94	112
75°	33	35	50	35
90°	0	0	0	0

cd / 1000 lm


LDC unsuitable for cone representation.
Asymmetric LDC.

η	LED
Efficiency	145 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	15 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	20.9
UGR C90/C270	24.3
CIE Flux Codes	58 85 97 100 100
Ra/CRI	>80

LTS

LK-L 060.10830.0985.1/DALI

Lichtkanal 060 | Light-Insert (AOV-002/005.2, 1xLED 15W 830/3000K 2160lm)



	C0	C90	C180	C270
0°	351	351	351	351
15°	332	328	332	328
30°	280	271	280	271
45°	213	200	213	200
60°	143	125	143	125
75°	74	51	74	51
90°	26	1	26	1

cd / 1000 lm


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	7.97 7.16	84.1
6.0	15.93 14.33	21.0
9.0	23.90 21.49	9.3
12.0	31.86 28.66	5.3
15.0	39.83 35.82	3.4

η	LED
Efficiency	144 lm/W
Direct/Indirect	↓ 93% / ↑ 7%
System Power	15 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	25.8
UGR C90/C270	24.1
CIE Flux Codes	48 78 94 93 100
Ra/CRI	>80

LTS

LK-L 060.10830.0985.1/DALI

Lichtkanal 060 | Light-Insert (Batwing/Wide Beam nanoOptix, 1xLED 15W 830/3000K 2290lm)



	C0	C90	C180	C270
0°	389	389	389	389
15°	482	373	482	373
30°	507	328	507	328
45°	102	243	102	243
60°	55	138	55	138
75°	21	53	21	53
90°	0	0	0	0

cd / 1000 lm


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	7.84 3.78	98.9
6.0	7.68 7.57	24.7
9.0	11.52 11.35	11.0
12.0	15.36 15.13	6.2
15.0	19.20 18.92	4.0

η	LED
Efficiency	153 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	15 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.1
UGR C90/C270	25.4
CIE Flux Codes	64 90 98 100 100
Ra/CRI	>80

LTS

LK-L 060.10830.0985.1/DALI

Lichtkanal 060 | Light-Insert (AOV-001/003/005.1, 1xLED 15W 830/3000K 2160lm)



	C0	C90	C180	C270
0°	351	351	351	351
15°	332	328	332	328
30°	280	271	280	271
45°	213	200	213	200
60°	143	125	143	125
75°	74	51	74	51
90°	26	1	26	1

cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	7.97 7.16	84.1
6.0	15.93 14.33	21.0
9.0	23.90 21.49	9.3
12.0	31.86 28.66	5.3
15.0	39.83 35.82	3.4


η	LED
Efficiency	144 lm/W
Direct/Indirect	↓ 93% / ↑ 7%
System Power	15 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	25.8
UGR C90/C270	24.1
CIE Flux Codes	48 78 94 93 100
Ra/CRI	>80

LTS

LK-L 060.10830.0985.1/DALI

LK-L 060.10830.0985.1/DALI

Lichtkanal 060 | Light-Insert (Opal Diffuse, 1xLED 15W 830/3000K 2180lm)



	C0	C90	C180	C270
0°	448	448	448	448
15°	414	422	414	422
30°	323	351	323	351
45°	214	253	214	253
60°	119	148	119	148
75°	42	58	42	58
90°	0	0	0	0
cd / 1000 lm				


Offset [m]	Cone width [m]		Illuminance [lx]
3.0	5.72	6.90	108.5
6.0	11.45	13.79	27.1
9.0	17.17	20.69	12.1
12.0	22.89	27.58	6.8
15.0	28.62	34.48	4.3

η	LED
Efficiency	145 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	15 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	23.5
UGR C90/C270	24.6
CIE Flux Codes	54 84 97 100 100
Ra/CRI	>80

LTS

LK-L 060.10830.0985.1/DALI

Lichtkanal 060 | Light-Insert (Deep Beam nanoOptix, 1xLED 15W 830/3000K 2270lm)



	C0	C90	C180	C270
0°	662	662	662	662
15°	624	670	624	670
30°	161	710	161	710
45°	100	843	100	843
60°	54	374	54	374
75°	25	42	25	42
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
3.0	2.33	9.68	166.9
6.0	4.66	19.36	41.7
9.0	6.99	29.04	18.5
12.0	9.32	38.72	10.4
15.0	11.65	48.39	6.7

η	LED
Efficiency	151 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	15 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.2
UGR C90/C270	24.2
CIE Flux Codes	68 90 98 100 100
Ra/CRI	>80

LTS