

LK-L 070.10830.0845.1/DALI



Description

- light-insert with integrated LED strips
- reflector made from traffic white painted aluminium sheet
- no UV and thermal emissions
- almost all strip light lengths can be realised
- 5-pole through-wiring kit included
- pMMA matt foil for uniform light distribution
- tool-free snapping into Lichtkanal profile via mounting springs
- 5-pole terminal block, pre-fabricated for through-wiring
- ballast (LED converter DALI, dimmable) integrated


Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $\Delta T = 10$ Kelvin.




Standard options

4000 K

Special options



Colours	Article no.	EAN
	668039	4043544796967



Lighting data / Norms

Lamps	LED linear / CRI 80 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	12.4 W
Luminaire luminous flux	max. 2000 lm
System efficiency	161.29 lm/W
Module efficiency	193.00 lm/W
UGR class	≤28
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I


Dimensions / Weights

Length	845 mm
Width	57 mm
Height	52 mm
Net weight	1.27 kg
Gross weight	1.34 kg

LK-L 070.10830.0845.1/DALI

LK-L 070.10830.0845.1/DALI

Lichtkanal 070 | Light-Insert (APB, 1xLED 12W 830/3000K 2000lm)



	C0	C90	C180	C270
0°	511	511	511	511
15°	491	492	491	492
30°	344	435	344	435
45°	171	317	171	317
60°	59	106	59	106
75°	24	37	24	37
90°	0	0	0	0

cd / 1000 lm


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	4.61 7.23	113.5
6.0	9.23 14.46	28.4
9.0	13.84 21.69	12.6
12.0	18.46 28.93	7.1
15.0	23.07 36.16	4.5

η	LED
Efficiency	167 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	20.1
UGR C90/C270	22.4
CIE Flux Codes	63 90 98 100 100
Ra/CRI	>80

LTS

LK-L 070.10830.0845.1/DALI

Lichtkanal 070 | Light-Insert (AOB, 1xLED 12W 830/3000K 1890lm)



	C0	C90	C180	C270
0°	404	404	404	404
15°	380	380	380	380
30°	314	316	314	316
45°	230	228	230	228
60°	144	140	144	140
75°	61	57	61	57
90°	1	1	1	1

cd / 1000 lm


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	7.11 7.01	84.9
6.0	14.22 14.02	21.2
9.0	21.33 21.02	9.4
12.0	28.43 28.03	5.3
15.0	35.54 35.04	3.4

η	LED
Efficiency	158 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	24.4
UGR C90/C270	24.1
CIE Flux Codes	51 81 96 100 100
Ra/CRI	>80

LTS

LK-L 070.10830.0845.1/DALI

Lichtkanal 070 | Light-Insert (AOV-002/005.2, 1xLED 12W 830/3000K 1790lm)



	C0	C90	C180	C270
0°	315	315	315	315
30°	262	238	262	238
60°	148	103	148	103
90°	44	1	44	1
120°	31	0	31	0
150°	16	1	16	1
180°	1	1	1	1

cd / 1000 lm


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	9.35 6.59	62.7
6.0	18.70 13.18	15.7
9.0	28.05 19.77	7.0
12.0	37.40 26.36	3.9
15.0	46.75 32.95	2.5

η	LED
Efficiency	149 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	25.9
UGR C90/C270	22.5
CIE Flux Codes	46 75 92 89 100
Ra/CRI	>80

LTS

LK-L 070.10830.0845.1/DALI

Lichtkanal 070 | Light-Insert (AOV-001/003/005.1, 1xLED 12W 830/3000K 1790lm)



	C0	C90	C180	C270
0°	315	315	315	315
30°	262	238	262	238
60°	148	103	148	103
90°	44	1	44	1
120°	31	0	31	0
150°	16	1	16	1
180°	1	1	1	1

cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	9.35 6.59	62.7
6.0	18.70 13.18	15.7
9.0	28.05 19.77	7.0
12.0	37.40 26.36	3.9
15.0	46.75 32.95	2.5

η	LED
Efficiency	149 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	25.9
UGR C90/C270	22.5
CIE Flux Codes	46 75 92 89 100
Ra/CRI	>80

LTS