




LK-L 070.11840.2245.1/DALI/NO



Colours	Article no.	EAN
	668081	4043544797384



Description

- light-insert with integrated LED strips
- reflector made from traffic white painted aluminium sheet
- no UV and thermal emissions
- almost all strip light lengths can be realised
- 5-pole through-wiring kit included
- emergency lighting LED Driver with DALI interface and automatic test function
- non-maintained operation
- DALI interface for controlled testing and monitoring (if the DALI bus is not connected, the unit will operate in self-test mode)
- rated duration: 3 h
- automatic shutdown of the output if LED load is out of range
- constant power output: 2.5 W
- luminous flux: 260 lm
- patented addressing function (EZ easy addressing)
- electronic multi-level charge system
- connection options
- batteries: high-temperature cells (NiMH batteries 4 Ah / 3.6 V)
- typ. power factor at 230 V / 50 Hz: 0.45
- time to light: < 0.25 s from detection of emergency event
- overvoltage protection :320 V for 1 h
- ambient temperature: -20...+45 °C
- lifetime: 4 years with maximum 2 discharges every year
- mains voltage changeover threshold according to EN 60598-2-22
- pMMA matt foil for uniform light distribution
- tool-free snapping into Lichtkanal profile via mounting springs
- 5-pole terminal block, pre-fabricated for through-wiring
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $\Delta T = 10$ Kelvin.

Standard options



Special options



Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	51.0 W
Luminaire luminous flux	max. 8690 lm
System efficiency	170.39 lm/W
Module efficiency	205.00 lm/W



LK-L 070.11840.2245.1/DALI/NO

UGR class	≤28
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I


Dimensions / Weights

Length	2245 mm
Width	57 mm
Height	52 mm
Net weight	3.43 kg
Gross weight	3.61 kg

LK-L 070.11840.2245.1/DALI/NO

LK-L 070.11840.2245.1/DALI/NO

Lichtkanal 070 | Light-Insert (APB, 1xLED 51W 840/4000K 8690lm)



	C0	C90	C180	C270
0°	505	505	505	505
15°	487	482	487	482
30°	340	421	340	421
45°	170	316	170	316
60°	59	109	59	109
75°	24	38	24	38
90°	1	0	1	0

cd / 1000 lm


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	4.63 7.36	488.0
6.0	9.25 14.72	122.0
9.0	13.88 22.08	54.2
12.0	18.51 29.44	30.5
15.0	23.14 36.80	19.5

η	LED
Efficiency	170 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	51 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	21.8
UGR C90/C270	24.3
CIE Flux Codes	63 89 98 100 100
Ra/CRI	>80

LTS

LK-L 070.11840.2245.1/DALI/NO

Lichtkanal 070 | Light-Insert (AOB, 1xLED 51W 840/4000K 8210lm)



	C0	C90	C180	C270
0°	400	400	400	400
15°	376	375	376	375
30°	310	308	310	308
45°	228	226	228	226
60°	142	141	142	141
75°	61	58	61	58
90°	1	1	1	1

cd / 1000 lm


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	7.15 7.08	364.6
6.0	14.31 14.16	91.1
9.0	21.46 21.25	40.5
12.0	28.62 28.33	22.8
15.0	35.77 35.41	14.6

η	LED
Efficiency	161 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	51 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	26.1
UGR C90/C270	26.0
CIE Flux Codes	50 81 96 100 100
Ra/CRI	>80

LTS

LK-L 070.11840.2245.1/DALI/NO

Lichtkanal 070 | Light-Insert (AOV-002/005.2, 1xLED 51W 840/4000K 7730lm)



	C0	C90	C180	C270
0°	312	312	312	312
30°	258	240	258	240
60°	146	106	146	106
90°	44	1	44	1
120°	30	0	30	0
150°	16	1	16	1
180°	1	1	1	1

cd / 1000 lm


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	9.32 6.81	268.3
6.0	18.63 13.62	67.1
9.0	27.95 20.44	29.8
12.0	37.26 27.25	16.8
15.0	46.58 34.06	10.7

η	LED
Efficiency	152 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	51 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	27.5
UGR C90/C270	24.4
CIE Flux Codes	45 75 92 89 100
Ra/CRI	>80

LTS

LK-L 070.11840.2245.1/DALI/NO

Lichtkanal 070 | Light-Insert (AOV-001/003/005.1, 1xLED 51W 840/4000K 7730lm)



	C0	C90	C180	C270
0°	312	312	312	312
30°	258	240	258	240
60°	146	106	146	106
90°	44	1	44	1
120°	30	0	30	0
150°	16	1	16	1
180°	1	1	1	1

cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	9.32 6.81	268.3
6.0	18.63 13.62	67.1
9.0	27.95 20.44	29.8
12.0	37.26 27.25	16.8
15.0	46.58 34.06	10.7

η	LED
Efficiency	152 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	51 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	27.5
UGR C90/C270	24.4
CIE Flux Codes	45 75 92 89 100
Ra/CRI	>80

LTS