


JETT-T 103.927.WF



Colours	Article no.	EAN
silver	668463	4043544801234
black	668464	4043544801241
white	668465	4043544801258

















Description

- flexible track-mounted spotlight in separated design with cylindrical light-head
- luminaire rotates through 355° and light-head pivots through 180°
- outstanding ease of maintenance
- no UV and thermal emissions
- light-head made from die-cast aluminium
- innovative thermal management with design-integrated passive cooling
- high performance specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- ballast housing made from sheet steel
- · clear safety glass
- 3-phase track adapter
- ballast (LED converter) integrated

Standard options













Special options











Lighting data / Norms

Lamps LED Spot / CRI 90 / 2700 K

EPREL light sources 1115627

L90 B50 50.000 h
Lifetime L80 B50 100.000 h
L80 B20 50.000 h

 System power
 24.1 W

 Luminaire luminous flux
 3020 lm

 System efficiency
 125.31 lm/W

 Module efficiency
 134.07 lm/W

 UGR class
 ≤22

 Beam range
 Wide Flood

 Beam angle
 50°

Supply voltage 220 - 240 V / 50 - 60 Hz

Protection class I
Type of protection IP20

Dimensions / Weights

 Length
 151 mm

 Width
 103 mm

 Height
 170 mm

 Diameter of light head
 103 mm

 Net weight
 1.28 kg


 Gross weight
 1.35 kg

LTS LOVE TO SHINE


JETT-T 103.927.WF

JETT-T 103.927.WF

Jett Evo | Track-Mounted (1xLED 24W 927/2700K 3020Im 50°)



	C0	C90	C180	C270
0°	1544	1544	1544	1544
15°	1274	1274	1274	1274
30°	487	487	487	487
45°	18	18	18	18
60°	8	8	8	8
75°	2	2	2	2
90°	0	0	0	0
	cc	i / 1000 l	m	



η	LED		
Efficiency	126 lm/W ↓ 100% / ↑ 0%		
Direct/Indirect			
System Power	24 W		
UGR	X=4H, Y=8H		
Reflection factors	70/50/20		
UGR C0/C180	19.6		
UGR C90/C270	19.6		
CIE Flux Codes	97 99 100 100 100		
Ra/CRI	>90		

LTS

Accessories



FOCUS 100.1

superior optic with focusable biconvex lens for accent lighting



ST-A 10/9000A-1-ST

surface-mounted track ONETrack Advance with data bus

(length: 1000 mm)



ST-A 20/9000A-2-ST

surface-mounted track ONETrack Advance with data bus (length: 2000 mm)



ST-A 30/9000A-3-ST

surface-mounted track ONETrack Advance with data bus

(length: 3000 mm)



ST-A 40/9000A-4-ST

surface-mounted track ONETrack Advance with data bus (length: 4000 mm)



ST-A MONO/9000-BPU-D

3-phase surface-mounted monopoint with bus option



ST-E 10/9000-1-R

recessed track ONETrack with data bus (length: 1000 mm)



ST-E 20/9000-2-R

recessed track ONETrack with data bus (length: 2000 mm)



ST-E 30/9000-3-R

recessed track ONETrack with data bus (length: 3000 mm)



ST-E 40/9000-4-R

recessed track ONETrack with data bus (length: 4000 mm)



ST-E MONO/9000-BPU-D

3-phase recessed monopoint with bus option



ZBK 96 anti-glare flaps

Track-Mounted Spotlights · Jett Evo Power Track



Accessories



ZBW 83 honeycomb louvre

