


STRL-J 103.30.50



Colours	Article no.	EAN
black	649546	4043544574466
silver	649547	4043544574473
white	649548	4043544574480



Description

- mounting spotlight for StraitLine 60 light-line with clear and cylindrical light-head design
- light-head rotates through 355° and pivots through 90°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- light-head made from die-cast aluminium
- ballast insertable into StraitLine profile
- clear and reflection-free EnergyVision safety glass
- tool-free mounting of the spotlight in profile
- simple plug connection (distributor connector included)
- ballast (LED converter) included

Notes

Not suitable for StraitLine profiles with a length of 845 mm. Profile with a length of 1125 mm are only suitable for one mounting spotlight.

Standard options



Special options



Lighting data / Norms

Lamps	LED Spot / CRI 80 / 3000 K
EPREL light sources	1070946
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	
System power	30.0 W
Luminaire luminous flux	2990 lm
System efficiency	99.66 lm/W
Module efficiency	166.62 lm/W
UGR class	≤22
Beam angle	50°
Supply voltage	220 - 240 V / 50 - 60 Hz

Protection class	I
Type of protection	IP20


Dimensions / Weights

Outer diameter	103 mm
Height	267 mm
Diameter of light head	103 mm
Net weight	1.28 kg
Gross weight	1.40 kg

STRL-J 103.30.50

StraitLine 60 - Mounting Spotlight (1xLED 30W 830/3000K 2990lm 50 °)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	1436	1436	1436	1436
15°	1224	1224	1224	1224
30°	507	507	507	507
45°	13	13	13	13
60°	5	5	5	5
75°	3	3	3	3
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]	Illuminance [lx]
C0-C180 Plane		
3.0	2.93	477.1
6.0	5.87	119.3
9.0	8.80	53.0
12.0	11.74	29.8
15.0	14.67	19.1

η	LED
Efficiency	100 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	30 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	20.3
UGR C90/C270	20.3
CIE Flux Codes	98 99 100 100 100
Ra/CRI	>80

LTS

Accessories



FOCUS 100.1
superior optic with focusable biconvex lens for
accent lighting



ZBK 96
anti-glare flaps



ZBW 83
honeycomb louvre