


## STRL-J 105.30.35



| Colours | Article no. | EAN           |
|---------|-------------|---------------|
| black   | 649576      | 4043544574763 |
| silver  | 649577      | 4043544574770 |
| white   | 649578      | 4043544574787 |



## Description

- mounting spotlight for StraitLine 60 light-line with clear and cylindrical light-head design
- light-head rotates through 355° and pivots through 90°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- light-head made from die-cast aluminium
- ballast insertable into StraitLine profile
- clear and reflection-free EnergyVision safety glass
- tool-free mounting of the spotlight in profile
- simple plug connection (distributor connector included)
- ballast (LED converter) included

## Notes

Not suitable for StraitLine profiles with a length of 845 mm. Profile with a length of 1125 mm are only suitable for one mounting spotlight.

## Standard options



## Special options



## Lighting data / Norms


|                         |                            |
|-------------------------|----------------------------|
| Lamps                   | LED Spot / CRI 80 / 3000 K |
| EPREL light sources     | 848104                     |
|                         | L90 B50 50.000 h           |
|                         | L80 B50 100.000 h          |
|                         | L80 B20 50.000 h           |
| Lifetime                |                            |
| System power            | 50.0 W                     |
| Luminaire luminous flux | 5470 lm                    |
| System efficiency       | 109.40 lm/W                |
| Module efficiency       | 163.73 lm/W                |
| UGR class               | ≤22                        |
| Beam angle              | 35°                        |
| Supply voltage          | 220 - 240 V / 50 - 60 Hz   |
| Protection class        | I                          |
| Type of protection      | IP20                       |

## Dimensions / Weights

|                        |         |
|------------------------|---------|
| Outer diameter         | 103 mm  |
| Height                 | 267 mm  |
| Diameter of light head | 103 mm  |
| Net weight             | 1.28 kg |
| Gross weight           | 1.40 kg |

# STRL-J 105.30.35

StraitLine 60 - Mounting Spotlight (1xLED 50W 830/3000K 5470lm 35 °)



|              | C0   | C90  | C180 | C270 |
|--------------|------|------|------|------|
| 0°           | 2403 | 2403 | 2403 | 2403 |
| 15°          | 1450 | 1450 | 1450 | 1450 |
| 30°          | 380  | 380  | 380  | 380  |
| 45°          | 8    | 8    | 8    | 8    |
| 60°          | 4    | 4    | 4    | 4    |
| 75°          | 2    | 2    | 2    | 2    |
| 90°          | 0    | 0    | 0    | 0    |
| cd / 1000 lm |      |      |      |      |

| Offset [m] | Cone width [m] | Illuminance [lx] |
|------------|----------------|------------------|
| 3.0        | 1.85           | 1460.7           |
| 6.0        | 3.70           | 365.2            |
| 9.0        | 5.54           | 162.3            |
| 12.0       | 7.39           | 91.3             |
| 15.0       | 9.24           | 58.4             |

|                    |                   |
|--------------------|-------------------|
| <b>η</b>           | LED               |
| Efficiency         | 110 lm/W          |
| Direct/Indirect    | ↓ 100% / ↑ 0%     |
| System Power       | 50 W              |
| <b>UGR</b>         | X=4H, Y=8H        |
| Reflection factors | 70/50/20          |
| UGR C0/C180        | 20.5              |
| UGR C90/C270       | 20.5              |
| CIE Flux Codes     | 98 99 100 100 100 |
| Ra/CRI             | >80               |

LTS

## Accessories



**FOCUS 100.1**  
superior optic with focusable biconvex lens for  
accent lighting



**ZBK 96**  
anti-glare flaps



**ZBW 83**  
honeycomb louvre