

# JETT-R 105.930.MF



Colours	Article no.	EAN
silver	668874	4043544805454
black	668875	4043544805461
white	668876	4043544805478



## Description

- flexible recessed spotlight with cylindrical light-head
- light-head completely extracts, rotates through 355° and pivots through 90°
- outstanding ease of maintenance
- no UV and thermal emissions
- light-head made from die-cast aluminium
- innovative thermal management with design-integrated passive cooling
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- recessed frame made from aluminium and sheet steel
- concealing plate for ceiling opening
- clear safety glass
- tool-free ceiling mounting via automatic quick clamping (automatic adjustment of the ceiling thickness)
- luminaire and ballast permanently connected via cable (length: 500 mm), ballast ready for mains connection
- ballast (LED converter) included (external placement)

## Standard options



## Special options



## Lighting data / Norms

<b>Lamps</b>	LED Spot / CRI 90 / 3000 K
<b>Lifetime</b>	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
<b>System power</b>	46.2 W
<b>Luminaire luminous flux</b>	5670 lm
<b>System efficiency</b>	122.72 lm/W
<b>Module efficiency</b>	138.00 lm/W
<b>UGR class</b>	≤25
<b>Beam range</b>	Medium Flood
<b>Beam angle</b>	26°
<b>Supply voltage</b>	220 - 240 V / 50 - 60 Hz
<b>Protection class</b>	II
<b>Type of protection</b>	IP20

## Dimensions / Weights


<b>Outer diameter</b>	170 mm
<b>Height</b>	198 mm
<b>Cut-out (Ø)</b>	145 mm
<b>Ceiling thickness</b>	5.0 - 50.0 mm
<b>Recessed depth</b>	195 mm
<b>Diameter of light head</b>	103 mm
<b>Net weight</b>	1.88 kg
<b>Gross weight</b>	1.98 kg

# JETT-R 105.930.MF

## JETT-R 105.930.MF

Jett Evo | Recessed (1xLED 46W 930/3000K 5670lm 26°)

— C0/C180    cd / 1000 lm



	C0	C90	C180	C270
0°	2976	2976	2976	2976
15°	1209	1209	1209	1209
30°	381	381	381	381
45°	19	19	19	19
60°	14	14	14	14
75°	6	6	6	6
90°	0	0	0	0
cd / 1000 lm				

Offset [m]    Cone width [m]    Illuminance [lx]

C0-C180 Plane		
3.0	1.39	1874.8
6.0	2.78	468.7
9.0	4.17	208.3
12.0	5.56	117.2
15.0	6.95	75.0

<b>η</b>	LED
Efficiency	124 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	46 W
<b>UGR</b>	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	23.0
UGR C90/C270	23.0
CIE Flux Codes	95 98 99 100 100
Ra/CRI	>90

LTS

## Accessories



**FOCUS 100.1**  
superior optic with focusable biconvex lens for  
accent lighting



**ZBK 96**  
anti-glare flaps



**ZBW 83**  
honeycomb louvre



**ZDAR 158.200-265**  
compensation ring for ceiling cut-outs from 200 to  
265 mm



**ZDVR 0157**  
ceiling reinforcement ring