


BIXXL 204.35.40.2/DALI-EU



Description

- flexible track-mounted spotlight in separated design with organically formed light-head
- luminaire rotates through 355° and light-head pivots through 90°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with design-integrated passive cooling
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- light-head made from die-cast aluminium
- ballast housing made from aluminium
- clear and reflection-free EnergyVision safety glass
- 3-phase track adapter DALI (Eutrac)
- ballast (LED converter DALI, dimmable) integrated

Standard options






Colours	Article no.	EAN
black	646422	4043544536471
silver	646423	4043544536488
white	646424	4043544536495

Lighting data / Norms

Lamps	LED Spot / CRI 80 / 3500 K
EPREL light sources	848112
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	41.0 W
Luminaire luminous flux	4220 lm
System efficiency	102.92 lm/W
Module efficiency	144.70 lm/W
Beam angle	40°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights


Length	136 mm
Width	170 mm
Height	195 mm
Diameter of light head	123 mm
Net weight	1.60 kg
Gross weight	1.80 kg



BIXXL 204.35.40.2/DALI-EU

BIXXL 200 Track-Mounted (1xLED 41W 835/3500K 4220lm)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	1684	1684	1684	1684
15°	1438	1438	1438	1438
30°	413	413	413	413
45°	7	7	7	7
60°	3	3	3	3
75°	3	3	3	3
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	2.46	789.6
6.0	4.91	197.4
9.0	7.37	87.7
12.0	9.82	49.4
15.0	12.28	31.6


η	LED
Efficiency	103 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	41 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	18.6
UGR C90/C270	18.6
CIE Flux Codes	98 99 100 100 100
Ra/CRI	>80

LTS

Accessories



ZBK 98
anti-glare flaps



ZBW 84
honeycomb louvre