

LK-L 045.10830.0985.1/DALI



Description

- light-insert made from sheet steel with integrated LED modules
- no UV and thermal emissions
- almost all strip light lengths can be realised
- 5-pole through-wiring kit included
- curved PMMA diffuser for uniform light distribution
- tool-free snap-in fastening into profile
- 5-pole terminal block, pre-fabricated for 5-pole through-wiring
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $\Delta T = 10$ Kelvin.

Standard options

4000 K

Special options

2700 K


CRI 90
SDCM3

TWL

MinusBlue



Colours	Article no.	EAN
	669403	4043544810793





Lighting data / Norms

Lamps	LED linear / CRI 80 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	14.3 W
Luminaire luminous flux	max. 2020 lm
System efficiency	141.25 lm/W
Module efficiency	193.00 lm/W
UGR class	≤28
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I

Dimensions / Weights


Length	985 mm
Width	43 mm
Height	44 mm
Net weight	0.84 kg
Gross weight	0.94 kg



LK-L 045.10830.0985.1/DALI

LK-L 045.10830.0985.1/DALI

Lichtkanal 045 | Light-Insert (AOB, 1xLED 14W 830/3000K 2020lm)



	C0	C90	C180	C270
0°	425	425	425	425
15°	397	400	397	400
30°	320	335	320	335
45°	223	244	223	244
60°	132	146	132	146
75°	54	57	54	57
90°	1	0	1	0

cd / 1000 lm


Offset [m]	Cone width [m]		Illuminance [lx]
3.0	C0-C180 Plane	C90-C270 Plane	95.5
6.0	12.71 14.13		23.9
9.0	19.06 21.19		10.6
12.0	25.41 28.26		6.0
15.0	31.76 35.32		3.8

η	LED
Efficiency	144 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	14 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	25.0
UGR C90/C270	25.1
CIE Flux Codes	52 82 96 100 100
Ra/CRI	>80

LTS

LK-L 045.10830.0985.1/DALI

Lichtkanal 045 | Light-Insert (AOV-001/003/005.1, 1xLED 14W 830/3000K 1910lm)



	C0	C90	C180	C270
0°	330	330	330	330
30°	259	251	259	251
60°	140	106	140	106
90°	45	1	45	1
120°	33	0	33	0
150°	16	1	16	1
180°	1	1	1	1

cd / 1000 lm


Offset [m]	Cone width [m]		Illuminance [lx]
3.0	C0-C180 Plane	C90-C270 Plane	70.1
6.0	16.09 13.11		17.5
9.0	24.13 19.67		7.8
12.0	32.18 26.23		4.4
15.0	40.22 32.78		2.8

η	LED
Efficiency	136 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	14 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	26.7
UGR C90/C270	23.4
CIE Flux Codes	47 76 92 89 100
Ra/CRI	>80

LTS

LK-L 045.10830.0985.1/DALI

Lichtkanal 045 | Light-Insert (APB, 1xLED 14W 830/3000K 1950lm)



	C0	C90	C180	C270
0°	549	549	549	549
15°	525	529	525	529
30°	384	461	384	461
45°	199	267	199	267
60°	69	76	69	76
75°	27	32	27	32
90°	0	0	0	0

cd / 1000 lm


Offset [m]	Cone width [m]		Illuminance [lx]
3.0	C0-C180 Plane	C90-C270 Plane	119.0
6.0	9.67 11.81		29.7
9.0	14.50 17.72		13.2
12.0	19.34 23.62		7.4
15.0	24.17 29.53		4.8

η	LED
Efficiency	139 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	14 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	21.3
UGR C90/C270	21.9
CIE Flux Codes	67 91 98 100 100
Ra/CRI	>80

LTS

LK-L 045.10830.0985.1/DALI

Lichtkanal 045 | Light-Insert (AOV-002/005.2, 1xLED 14W 830/3000K 1910lm)



	C0	C90	C180	C270
0°	330	330	330	330
30°	259	251	259	251
60°	140	106	140	106
90°	45	1	45	1
120°	33	0	33	0
150°	16	1	16	1
180°	1	1	1	1

cd / 1000 lm

Offset [m]	Cone width [m]		Illuminance [lx]
3.0	C0-C180 Plane	C90-C270 Plane	70.1
6.0	16.09 13.11		17.5
9.0	24.13 19.67		7.8
12.0	32.18 26.23		4.4
15.0	40.22 32.78		2.8

η	LED
Efficiency	136 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	14 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	26.7
UGR C90/C270	23.4
CIE Flux Codes	47 76 92 89 100
Ra/CRI	>80

LTS