

LK-L 045.11830.1125.1/DALI



Description

- light-insert made from sheet steel with integrated LED modules
- no UV and thermal emissions
- almost all strip light lengths can be realised
- 5-pole through-wiring kit included
- curved PMMA diffuser for uniform light distribution
- tool-free snap-in fastening into profile
- 5-pole terminal block, pre-fabricated for 5-pole through-wiring
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $\Delta T = 10$ Kelvin.

Standard options

4000 K

Special options

2700 K


CRI 90
SDCM3

TWL

MinusBlue



Colours	Article no.	EAN
	669417	4043544810939





Lighting data / Norms

Lamps	LED linear / CRI 80 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	25.2 W
Luminaire luminous flux	max. 3530 lm
System efficiency	132.53 lm/W
Module efficiency	193.00 lm/W
UGR class	≤28
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I

Dimensions / Weights


Length	1125 mm
Width	43 mm
Height	44 mm
Net weight	0.98 kg
Gross weight	1.18 kg



LK-L 045.11830.1125.1/DALI

LK-L 045.11830.1125.1/DALI

Lichtkanal 045 | Light-Insert (AOV-002/005.2, 1xLED 25W 830/3000K 3340lm)



	C0	C90	C180	C270
0°	331	331	331	331
30°	259	252	259	252
60°	140	109	140	109
90°	45	1	45	1
120°	33	0	33	0
150°	16	0	16	0
180°	1	1	1	1
cd / 1000 lm				


Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	8.04	6.70	122.9
6.0	16.09	13.41	30.7
9.0	24.13	20.11	13.7
12.0	32.18	26.82	7.7
15.0	40.22	33.52	4.9

η	LED
Efficiency	134 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	25 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	28.2
UGR C90/C270	24.9
CIE Flux Codes	47 76 92 89 100
Ra/CRI	>80

LTS

LK-L 045.11830.1125.1/DALI

Lichtkanal 045 | Light-Insert (AOV-001/003/005.1, 1xLED 25W 830/3000K 3340lm)



	C0	C90	C180	C270
0°	331	331	331	331
30°	259	252	259	252
60°	140	109	140	109
90°	45	1	45	1
120°	33	0	33	0
150°	16	0	16	0
180°	1	1	1	1
cd / 1000 lm				


Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	8.04	6.70	122.9
6.0	16.09	13.41	30.7
9.0	24.13	20.11	13.7
12.0	32.18	26.82	7.7
15.0	40.22	33.52	4.9

η	LED
Efficiency	134 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	25 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	28.2
UGR C90/C270	24.9
CIE Flux Codes	47 76 92 89 100
Ra/CRI	>80

LTS

LK-L 045.11830.1125.1/DALI

Lichtkanal 045 | Light-Insert (APB, 1xLED 25W 830/3000K 3390lm)



	C0	C90	C180	C270
0°	548	548	548	548
15°	526	533	526	533
30°	377	468	377	468
45°	198	271	198	271
60°	68	78	68	78
75°	27	33	27	33
90°	1	0	1	0
cd / 1000 lm				


Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	4.78	5.95	206.5
6.0	9.56	11.91	51.6
9.0	14.35	17.86	22.9
12.0	19.13	23.82	12.9
15.0	23.91	29.77	8.3

η	LED
Efficiency	136 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	25 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.7
UGR C90/C270	23.4
CIE Flux Codes	67 91 98 100 100
Ra/CRI	>80

LTS

LK-L 045.11830.1125.1/DALI

Lichtkanal 045 | Light-Insert (AOB, 1xLED 25W 830/3000K 3530lm)



	C0	C90	C180	C270
0°	421	421	421	421
15°	394	399	394	399
30°	317	339	317	339
45°	222	250	222	250
60°	131	150	131	150
75°	54	60	54	60
90°	1	0	1	0
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	6.36	7.37	164.9
6.0	12.73	14.73	41.2
9.0	19.09	22.10	18.3
12.0	25.45	29.47	10.3
15.0	31.82	36.83	6.6

η	LED
Efficiency	141 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	25 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	26.5
UGR C90/C270	26.7
CIE Flux Codes	52 82 96 100 100
Ra/CRI	>80

LTS