


ALF 106.1145.840



FAGERHULT

Colours	Article no.	EAN
white	670630	4043544822970



Description

- ceiling luminaire in a modern design with highly efficient LED technology
- internally switchable from 38 W to 28 W system power
- easy maintenance
- no UV and thermal emissions
- housing made from white enamelled and corrosion resistant aluminium zinc
- end covers made from polypropene
- wall brackets and wire-rope suspension available as accessories
- two feeding possibilities on the upper side of the housing
- luminaire provided for 2 x 2.5mm² through-wiring
- clear prismatic acrylic glass diffuser (optional: opal insert diffuser)
- direct screw mounting on ceiling (with supplied seals IP44)
- 5-pole terminal block
- ballast (LED converter) integrated

Notes

When using an opal diffuser the luminous flux is reduced by 1000 lm.

Standard options





Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
Lifetime	L81 B50 100.000 h
System power	38.0 W
Luminaire luminous flux	6200 lm
System efficiency	163.15 lm/W
UGR class	≤25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Impact resistance	IK03
Type of protection	IP44

Dimensions / Weights


Length	1145 mm
Width	130 mm
Height	49 mm
Net weight	2.20 kg
Gross weight	2.31 kg



ALF 106.1145.840

ALF 106.1145.840

AllFive (1xLED 38W 840/4000K 6200lm)



	C0	C90	C180	C270
0°	378	378	378	378
15°	363	364	363	364
30°	310	327	310	327
45°	220	251	220	251
60°	141	107	141	107
75°	66	34	66	34
90°	25	0	25	0
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
3.0	7.00	7.32	260.2
6.0	14.00	14.64	65.1
9.0	21.01	21.96	28.9
12.0	28.01	29.28	16.3
15.0	35.01	36.60	10.4

η	LED
Efficiency	163 lm/W
Direct/Indirect	↓ 96% / ↑ 4%
System Power	38 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	23.2
UGR C90/C270	22.5
CIE Flux Codes	53 82 95 96 100
Ra/CRI	>80

LTS

Accessories



ALF-Z10.03
wire-rope kit 2-fold



ALF-Z10.04
wall brackets
(2 pieces)



ALF-Z10.11-1145
prismatic diffuser
(as spare)



ALF-Z10.15-1145
insert diffuser opal