




ML-A 060.11830.2 OPD/DALI



Colours	Article no.	EAN
silver anodised	670437	4043544821058
black	670438	4043544821065
white	670439	4043544821072



Description

- filigree linear luminaire for surface mounting
- symmetrical light distribution and uniform area illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- housing made from aluminium
- end covers made from polycarbonate
- light-control foil "opal diffuse" with scattering additive made from polycarbonate
- easy mounting via supplied mounting brackets (2 pieces)
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $dT = 10$ Kelvin.

Standard options



Special options



Lighting data / Norms

Lamps	LED linear / CRI 80 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	25.5 W
Luminaire luminous flux	3820 lm
System efficiency	149.80 lm/W
Module efficiency	193.00 lm/W
UGR class	≤28
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Length	1140 mm
Width	60 mm
Height	50 mm
Net weight	2.70 kg
Gross weight	3.10 kg

ML-A 060.11830.2 OPD/DALI

ML-A 060.11830.2 OPD/DALI

Monoline 060 | Surface-Mounted (1xLED 26W 830/3000K 3820lm)



	C0	C90	C180	C270
0°	444	444	444	444
15°	410	419	410	419
30°	322	351	322	351
45°	212	254	212	254
60°	118	151	118	151
75°	42	59	42	59
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	5.73	7.06	188.5
6.0	11.45	14.13	47.1
9.0	17.18	21.19	20.9
12.0	22.91	28.25	11.8
15.0	28.63	35.31	7.5

η	LED
Efficiency	147 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	26 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	24.9
UGR C90/C270	26.2
CIE Flux Codes	54 84 97 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-A SENSOR
Organic Response sensor for surface mounting