

ML-E 060.10840.2 OPD/DALI



Description

- filigree linear luminaire for recessed mounting
- symmetrical light distribution and uniform area illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- aluminium housing with filigree trim (4.5 mm)
- end covers made from polycarbonate
- light-control foil "opal diffuse" with scattering additive made from polycarbonate
- easy quick-mounting in plasterboard with clamps
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $\Delta T = 10$ Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

Standard options



Special options



Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	16.5 W
Luminaire luminous flux	2640 lm
System efficiency	160.00 lm/W
Module efficiency	205.00 lm/W
UGR class	≤25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20




Dimensions / Weights

Length	1149 mm
Width	69 mm
Height	55 mm
Cut-out (LxW)	1142 x 64 mm
Ceiling thickness	5.0 - 25.0 mm
Recessed depth	82 mm
Net weight	2.80 kg
Gross weight	3.22 kg

Special dimensions

required clamps space: max. 141 mm


Colours	Article no.	EAN
silver anodised	670503	4043544821713
black	670504	4043544821720
white	670505	4043544821737



ML-E 060.10840.2 OPD/DALI

ML-E 060.10840.2 OPD/DALI

Monoline 060 | Recessed (1xLED 17W 840/4000K 2640lm)



	C0	C90	C180	C270
0°	448	448	448	448
15°	414	422	414	422
30°	323	351	323	351
45°	214	253	214	253
60°	119	148	119	148
75°	42	58	42	58
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	5.72	6.90	131.4
6.0	11.45	13.79	32.9
9.0	17.17	20.69	14.6
12.0	22.89	27.58	8.2
15.0	28.62	34.48	5.3

η	LED
Efficiency	155 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	17 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	23.7
UGR C90/C270	24.8
CIE Flux Codes	54 84 97 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting