


ML-E 060.11840.3 AOV/DALI



Colours	Article no.	EAN
silver anodised	670546	4043544822130
black	670547	4043544822147
white	670548	4043544822154



Description

- filigree linear luminaire for recessed mounting
- symmetrical light distribution and uniform area illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- aluminium housing with filigree trim (4.5 mm)
- end covers made from polycarbonate
- opal acrylic glass diffuser protruding (10 mm) made from PMMA with tool-free snap-in technology
- easy quick-mounting in plasterboard with clamps
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $dT = 10$ Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

Standard options



Special options



Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	31.9 W
Luminaire luminous flux	5010 lm
System efficiency	157.05 lm/W
Module efficiency	205.00 lm/W
UGR class	≤25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP40

Dimensions / Weights

Length	1429 mm
Width	69 mm
Height	65 mm
Cut-out (LxW)	1422 x 64 mm
Ceiling thickness	5.0 - 25.0 mm
Recessed depth	82 mm
Net weight	3.83 kg
Gross weight	4.35 kg


Special dimensions

required clamps space: max. 141 mm

ML-E 060.11840.3 AOV/DALI

ML-E 060.11840.3 AOV/DALI

Monoline 060 | Recessed (1xLED 32W 840/4000K 5010lm)



	C0	C90	C180	C270
0°	350	350	350	350
15°	332	328	332	328
30°	281	271	281	271
45°	213	200	213	200
60°	143	125	143	125
75°	75	51	75	51
90°	26	1	26	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
3.0	7.98	7.14	194.9
6.0	15.95	14.28	48.7
9.0	23.93	21.42	21.7
12.0	31.91	28.56	12.2
15.0	39.88	35.70	7.8

η	LED
Efficiency	157 lm/W
Direct/Indirect	↓ 93% / ↑ 7%
System Power	32 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	25.0
UGR C90/C270	24.1
CIE Flux Codes	48 78 94 93 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting