

ML-E 070.10840.2 AOV/DALI



Description

- linear luminaire for recessed mounting into plasterboard
- symmetrical light distribution and illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- aluminium housing with filigree trim (5 mm)
- end covers made from die-cast zinc
- opal protruding acrylic glass diffuser (19 mm) with profile guide and tool-free snap-in technology
- quick-mounting via clamps
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $dT = 10$ Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

Standard options



Special options



Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	16.5 W
Luminaire luminous flux	2520 lm
System efficiency	152.72 lm/W
Module efficiency	205.00 lm/W
UGR class	≤ 25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP40




Dimensions / Weights

Length	1146 mm
Width	80 mm
Height	99 mm
Cut-out (LxW)	1138 x 74 mm
Ceiling thickness	6.0 - 25.0 mm
Recessed depth	100 mm
Net weight	4.46 kg
Gross weight	4.89 kg

Special dimensions

required clamps space: max. 220 mm


Colours	Article no.	EAN
silver anodised	670278	4043544819468
black	670279	4043544819475
white	670280	4043544819482



ML-E 070.10840.2 AOV/DALI

ML-E 070.10840.2 AOV/DALI

Monoline 070 | Recessed (1xLED 17W 840/4000K 2520lm)



	C0	C90	C180	C270
0°	315	315	315	315
30°	262	238	262	238
60°	148	103	148	103
90°	44	1	44	1
120°	31	0	31	0
150°	16	1	16	1
180°	1	1	1	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	9.35	6.59	88.3
6.0	18.70	13.18	22.1
9.0	28.05	19.77	9.8
12.0	37.40	26.36	5.5
15.0	46.75	32.95	3.5

η	LED
Efficiency	148 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	17 W

UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	23.0
UGR C90/C270	21.0

CIE Flux Codes	46 75 92 89 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting