

ML-P 070.11840.2 AOB/DALI



Description

- linear luminaire for pendant mounting
- symmetrical light distribution and illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- housing made from aluminium
- end covers made from die-cast zinc
- opal flush acrylic glass diffuser with profile guide and tool-free snap-in technology
- wire-rope suspension 2-fold with height-adjustment (length: 3000 mm)
- pre-fabricated 5-core connecting cable transparent, ceiling box with feed-in made from ABS in the same colour as the luminaire
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $dT = 10$ Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

Standard options



Special options




Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	25.5 W
Luminaire luminous flux	4110 lm
System efficiency	161.17 lm/W
Module efficiency	205.00 lm/W
UGR class	≤28
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP40

Dimensions / Weights

Length	1136 mm
Width	70 mm
Height	80 mm
Net weight	4.55 kg
Gross weight	4.98 kg


Colours	Article no.	EAN
silver anodised	670383	4043544820518
black	670384	4043544820525
white	670385	4043544820532



ML-P 070.11840.2 AOB/DALI

ML-P 070.11840.2 AOB/DALI

Monoline 070 | Pendant (1xLED 26W 840/4000K 4110lm)



	C0	C90	C180	C270
0°	400	400	400	400
15°	376	375	376	375
30°	310	308	310	308
45°	228	226	228	226
60°	142	141	142	141
75°	61	58	61	58
90°	1	1	1	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	7.15	7.08	182.5
6.0	14.31	14.16	45.6
9.0	21.46	21.25	20.3
12.0	28.62	28.33	11.4
15.0	35.77	35.41	7.3

η	LED
Efficiency	158 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	26 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	26.1
UGR C90/C270	26.0
CIE Flux Codes	50 81 96 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-A SENSOR
Organic Response sensor for surface mounting



ZB-OR-P SENSOR/3000
Organic Response sensor for pendant mounting