


DWI-C 102.1164.840/DALI



Colours	Article no.	EAN
white	667602	4043544769008







Description

- dimmable corner luminaire in rectangular design for direct lighting of workplaces
- outstanding ease of maintenance
- no UV and thermal emissions
- housing made from sheet steel
- die-cast end covers with cable inlet for mains connection cable (1-phase through-wiring possible)
- anti-glare technology with double optics made from polycarbonate
- diffuser made from microprismatic acrylic glass with matt foil
- direct screw mounting in ceiling-wall transition
- 5-pole terminal block
- ballast (LED converter) integrated (with DALI dimming)

Standard options

3000 K

Lighting data / Norms

Lamps	LED Modul / CRI 80 / 4000 K
Lifetime	L100 B50 100.000 h
System power	21.0 W
Luminaire luminous flux	2940 lm
System efficiency	143.41 lm/W
UGR class	>28
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Length	1164 mm
Width	126 mm
Height	66 mm
Net weight	3.29 kg
Gross weight	3.46 kg

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024

DWI-C 102.1164.840/DALI

Dwide | Ecke (1xLED 21W 840/4000K 2940lm)



	C0	C90	C180	C270
0°	241	241	241	241
15°	389	218	101	213
30°	465	153	46	148
45°	481	91	0	88
60°	459	50	1	48
75°	387	20	3	18
90°	225	1	3	1

cd / 1000 lm

LDC unsuitable for cone representation.
Asymetric LDC.

η	LED
Efficiency	140 lm/W
Direct/Indirect	↓ 91% / ↑ 9%
System Power	21 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	33.8
UGR C90/C270	19.6
CIE Flux Codes	37 66 87 91 100
Ra/CRI	>80

LTS

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024