


CE COMPLIANT

REFURBISHMENT INSERT  
FOR THE QUICK REPLACEMENT  
OF YOUR T8 LAMPS



# RENOV8

RENOVATE LIGHT — SAFE AND  
WITHOUT COMPROMISES



LTS

# RENOV8

## REFURBISHMENT INSERT FOR THE QUICK T8 LED-UPGRADE

The Renov8 light insert from LTS is designed for the quick, easy, and CE-compliant replacement of double-ended T8 fluorescent tubes: The existing lamp holder is retained, and the Renov8 insert is fitted without tools in place of the T8 tube and secured with magnetic holders.

Advantages of refurbishing with Renov8:

### CE CONFORMITY AND MAINTENANCE OF THE OPERATING LICENCE

By using the Renov8 refurbishment insert, the operating licence of the luminaire fitted with Renov8 remains valid.

### HIGH EFFICIENCY OF YOUR LIGHTING

The high quality of the Renov8 light insert from LTS, equipped with the latest generation of high-quality LEDs, guarantees high operating efficiency and a long service life of up to 50,000 hours.

### OPTIMUM LIGHT QUALITY

LED complete luminaires from LTS are an overall system designed to continuously deliver maximum light quality with highest luminous efficacy.

### LTS REFURBISHING SOLUTIONS – WITH MANUFACTURER'S GUARANTEE

Renov8 is particularly suitable for refurbishing louvre luminaires. Available in three performance levels and three lengths, we offer the matching LED light insert for T8 tubes:

Length/wattage: 1500 mm/58W, 1200 mm/36W and 590 mm/18W

For upgrading T5 and T16 lamps we can offer refurbishment inserts on request.

### WE ARE HAPPY TO ADVISE YOU COMPREHENSIVELY

LTS Technical Service:  
+49 7542 9307-514

LTS Quotes Service:  
+49 7542 9307-508

By email:  
anfrage@lts-light.com

### RENOV8 ONLINE




All information can be found at  
[www.lts-light.com/en/renov8](http://www.lts-light.com/en/renov8)



	REPLACEMENT FOR T8 / 58 W	REPLACEMENT FOR T8 / 36 W	REPLACEMENT FOR T8 / 18 W
LENGTH (mm)	1405	1125	565
SYSTEM POWER	20,5 W *	16,4 W *	8,2 W *
LUMINOUS FLUX AT 4000 K	3740 lm *	2990 lm *	1500 lm *
EFFICIENCY AT 4000 K	182 lm/W *	182 lm/W *	183 lm/W *
DALI	Standard	Standard	Standard
CRI	80	80	80
COLOUR TEMPERATURE	3000 K, 4000 K	3000 K, 4000 K	3000 K, 4000 K

\* Maximum value





A Fagerhult Group Company

LTS Licht & Leuchten GmbH  
Waldesch 24  
88069 Tett nang  
Germany

T +49 7542 9307-0  
info@lts-light.com  
lts-light.com