


Encastrément

ML-E 070.10830.3 19P/DALI

ML-E 070.10830.3 19P/DALI

Monoline 070 | Recessed (1xLED 15W 830/3000K 2270lm)



	C0	C90	C180	C270
0°	649	649	649	649
15°	643	614	643	614
30°	416	397	416	397
45°	166	196	166	196
60°	49	64	49	64
75°	19	24	19	24
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
3.0	4.26	4.13	163.6
6.0	8.52	8.28	40.9
9.0	12.78	12.41	18.2
12.0	17.03	16.55	10.2
15.0	21.29	20.69	6.5

η	LED
Efficiency	151 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	15 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	17.7
UGR C90/C270	18.6
CIE Flux Codes	72 93 98 100 100
Ra/CRI	>80

LTS

Accessoires



ZB-OR DONGLE
Organic Response kit dongle IR



ZB-OR GATEWAY
Organic Response passerelle IoT série Cascade



ZB-OR-R SENSOR
capteur Organic Response pour montage encastré